

AQ-7M

Stainless Steel Side Seal Strapping Machine



Features

- Stainless steel body and parts help prevent rust and corrosion from moist environments.
- Heater ready in 25 seconds from start up
- Tension is easily adjusted via a conveniently positioned dial
- Able to handle 30 straps per minute
- Can operate with a wide variety strap (5mm to 19mm)

AQ-7M

Stainless Steel Side Seal Strapping Machine

Standard Features

Stainless steel body panels and parts made of stainless steel, aluminum and plastic make the StraPack AQ-7M the ideal machine for harsh environments. The bottom of the cabinet is reinforced to provide extra protection where moisture exposure is greatest. The cabinet is fully enclosed to protect the components from water and wash-down spray. An internal heat lamp assists in evaporating whatever moisture accumulates inside the machine.

The sealing head is side mounted to protect it from moisture and residue. The AQ-7M can strap boxes as small as 3 1/8" high. The roller table height is adjustable and can be removed to fit the AQ-7M into an existing conveyor system.

Tension on the AQ-7M is applied with a gripper and tension arm. This assures positive and accurate tensioning of damp strapping.

In the moisture-laden environments of poultry, meat and seafood processing the AQ-7M is the most durable strapping machine available. The corrosion free, low maintenance delivers results in dependable packaging.

Specifications

Machine Dimensions	1580mm W x 1782mm H x 610mm D (62 3/16" W x 70 1/8" H x 24" D)
Weight	200 kg (440 lbs)
Table Height	624, 642, 664 mm (24 9/16", 25 5/16", 26 1/8")
Arch Size	700mm W x 650 mm H (27 1/2" W x 25" H)
Min Package Size	30mm W x 80mm H (1 1/4" W x 3 1/8" H)
Max Package Size	680mm W x 500mm H (26 11/16" W x 19 11/16" H)
Strap Width	5,6,9,12,15.5 mm (1/4, 3/8, 1/2, 5/8")
Power Supply	200, 220, 240, 380, 400, 415V 3 phase 50/60Hz 0.85KVA