

## D-53PLT2

Portable Pallet Strapping Machine

---



### Features

- Can be used with 12mm (1/2") to 15.5mm (5/8") strapping
- Tension range can be limited in order to prevent package damage
- Tension is easily adjustable by a the Operation Bar, allowing edge protection to be secured to the pallet.
- Operator friendly! Use of Operation Bar and Start Switch are only needed for complete strap operation.

## D-53PLT2

### Portable Pallet Strapping Machine

---

#### Standard Features

The D-53PLT2 is designed to economically and quickly strap most kinds of pallets and skids using standard or heavier polypropylene strapping.

The D-53PLT2 can cut the time it takes to strap pallets up to by 2/3 when compared to hand tools. Its simple operation entails pushing the track into the pallet void, pressing a button to feed the strap, and inserting the tip of the strap in the machine - and within 2 seconds your strap operation is completed.

The D-53PLT2's unique design enables to strap pallets as low as 380mm or 15".

Arch track is retractable with a hand-crank. The height of the track is also adjustable to two positions depending on the type of the pallet or size of its void.

For edge protection insertion, the manual mode can be selected to control strap completion.

#### Specifications

Machine Dimensions	2195mm W x 1208mm H x 542mm D (86 5/8" x 46 5/8" x 21 3/8")
Weight	95 kg (205lbs)
Bayonet Height	10, 22.5, 35mm (3/8, 7/8, 1 3/8")
Package Size (Height)	380mm (15") - Unlimited
Strap Width	12, 15.5mm (1/2, 5/8")
Power Supply	100, 110, 120, 200, 220, 230, 240V Single Phase 60/60Hz 0.4kw