

MODEL P326

Battery Powered Plastic Strapping Tool



Features

- All new lithium ion battery technology featuring user friendly charge indicator
- New reinforced 18V motor
- Easy strap threading
- Adjustable sealing time for high sealing efficiency
- Suitable for polypropylene polyester, plain and embossed strapping
- Up to 600 strap cycles per battery load
- Easy tension adjustment, to ensure the right strap tension for safe operation

Model P326

Battery Powered Plastic Strapping Tool

Standard Features

Samuel Strapping Systems is proud to introduce the P326 hand held battery operated tool.

This robust tool provides unparalleled performance with tension ratings not previously attainable. Coupled with exceptional industry leading speed the P326 is the perfect hand held tool to apply our 3/8" to 5/8" plastic strapping

With the latest Lithium ion battery technology you can expect your tool to last longer in the field and recharge in a fraction of the time compared to traditional battery operated tools.

Specifications

Dimensions:	Length: 350 mm – 13.8" Width: 122mm – 4.8" Height: 130mm – 5"
Weight:	3.95 kg/ 8.7 lbs. (ind. battery)
Suitable strap qualities:	Polypropylene and Polyester, plain and embossed
Tension:	400 – 2400 N (90 – 540lbs) individual adjustment (Max. tension depends on strap quality)
Average sealing strength:	approx. 75% of strap breaking strength (dependent on strap quality)
Tension speed in seconds:	85-190 mm/s (3.3-7.5"/s)

Seal Joint

The advanced friction welding sealing technology guarantees a high seal joint efficiency.

Item No.	Model	Strap Width		Strap Thickness		Max Tension		Tension	Speed
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2201	P326/10/0.4-0.64	10	3/8"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2202	P326/10/0.65-1.05	10	3/8"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2211	P326/11.1/0.4-0.64	11.1	7/16"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2212	P326/11.1/0.65-1.05	11.1	7/16"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2223	P326/12.7/0.4-0.64	12.7	1/2"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2224	P326/12.7/0.65-1.05	12.7	1/2"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2261	P326/16/0.4-0.64	16	5/8"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2262	P326/16/0.65-1.05	16	5/8"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5

Accessories/Charging Units

Item No.	Description	Voltage/Frequency
N5.4330	P326 spare battery (Accu Li-Ion)	18 VDC/3.0 Ah
N5.4447	P326 battery charger	120 V/50-60 Hz
P32.0137	Suspension bracket for alternating positions	
P32.0112	Suspension bracket for standard working position	



Recharging time: approx. 1 hour
Battery life: approx. 500 charges