

MODEL RQ-8IR3

High Speed & Compact Model for Printing and Mailing Industry



Features

- Newly designed special high-speed sealing head can achieve 60 bundles per minute
- Integrated foot pedal under the body provides hand free operation
- Easy installation and operation
- Single dial provides a wide range of tension for all packages
- Takes only 25 seconds to reach operating temperature
- Self Diagnostic mechanism monitors critical functions and any irregularity detected is immediately displayed

Model RQ-8IR3

High Speed & Compact Model for Printing and Mailing Industry

Features

The newly designed special high-speed sealing head can achieve 60 bundles per minute without compromising on the tension strength.

Integrated foot pedal under the body as well as internal reel assures a safe operation.

The handles on both sides of the machine body together with oversized casters make the machine easy to maneuver in a limited space.

Specifications

Min. Bundle Dimensions	W 80 mm x H 30 mm (W 3 1/8" x H 1 1/8")
Max. Bundle Dimensions	W 620 mm x 500 mm (W 24 1/2" x H 19")
Table Height	936 mm (36 7/8")
Tensioning Range	Up to 35 kg (77 lbs)
Strapping Speed	Up to 60 straps per minute
Strapping Used	5,6 mm (1/4")
Power Supply	100-120, 200-240V Single Phase
Arch Size	W 650 mm x 400 mm (W 25" x H 16")
Machine Dimensions	W 1052mm x H 1445mm x D 609mm (W 41 3/8" x H 56 7/8" x D 24")



Distributed By: