



RQ-8IR2

Compact Strapping Machine



Features

- Easy strap width conversion from 5mm to 15.5 mm. No extra parts required
- Straps quickly at 1.5 seconds per strap
- Can work with common household power supply
- Automatic refeed of strapping
- Compact design helps save space with coil sitting within the body of the machine

RQ-8IR2

Compact Strapping Machine

Standard Features

The RQ-8IR2 is compact, with the coil located inside the machine. It takes up the space of a string tyer. The RQ8-IR II is designed for graphic arts, magazine and newspaper distribution and the direct mail industry. The internal dispenser makes the RQ-8IR II ideal for office applications, it is often used to bundle office reports and publications. It runs inexpensive 5mm, 6mm or 9mm strapping.

Mail flats easily fit into the 27" wide by 16" high arch. The angled sides of the RQ-8IR II arch support the sides of mail trays during strapping.

With the addition of a programmable photocell, the operator is free to use both hands on the package and can apply one or two straps without using a hand switch or foot pedal.

Specifications

Machine Dimensions	916mm W x 1393mm H x 609mm D (36 1/16" W x 54 7/8" H x 24" D)
Weight	168 kg (370lbs)
Table Height	884 mm (34 7/8")
Arch Size	690mm W x 400 mm H (27 1/8" W x 16" H)
Min Package Size	80mm W x 30mm H (3 1/8" W x 1 3/16" H)
Max Package Size	620mm W x 380mm H (24 7/16" W x 15" H)
Strap Width	5,6,9,12mm (1/4, 3/8, 1/2")
Strap Tension	Max 80kg (Max 176 lbs)
Speed	1.5 seconds/strap, 40 straps per minute
Power Supply	100, 100, 200, 220 V 1 phase 50/60Hz 0.65KVA