

MODEL RQ-8LD/LS

Automatic Low Body Strapping Machine

Features

- Capable of 1.8 straps/second
- Unlike a side seal machine, package does not need to be shifted against the sealing head
- Ideal for strapping heavy and/or bulk packages
- Up to 178 lbs of strap tension



RQ-8LD (with a separate pool box and dispenser)



RQ-8LS (with a docked pool box and dispenser)

Model RQ-8LD/LS

Automatic Low Body Strapping Machine

Product Features

When your applications require a low conveyor height and a bottom seal strapping machine, the RQ-8 low table models are the perfect machines. With a cabinet height of only 432mm or 17", the RQ-8L is unique. Unlike side-seal machines, the package does not have to be shifted against the sealing head.

Products longer than approx. 914mm or 36" can be strapped automatically by interlocking a standard RQ-8L to adjacent powered conveyor. For shorter packages, the RQ-8L can be built with the powered belt tabletops and automation features of the RQ-8A series.



RQ-8LD Shown.

Specifications RQ-8LD

Min. Package Size	W 80 mm x H 30 mm (W 3 1/8" x H 1 1/8")
Maximum Strap Tension	784N (178lbs)
Table Height	432mm (17")
Tensioning Range	Up to 40 kg (88 lbs)
Strapping Speed	1.8 seconds/strap
Strapping Used	5,6,9,12, 15.5mm (1/4, 3/8, 1/2, 5/8")
Power Supply	100-120, 200-240V Single Phase, 50-60Hz
Arch Size	W 850 mm x H 600 mm (W 33" x H 24")
Machine Dimensions	W 1863mm x H 1547mm x D 609mm (W 73 3/8" x H 60 7/8" x D 24")

Specifications RQ-8LS

Min. Package Size	W 80 mm x H 30 mm (W 3 1/8" x H 1 1/8")
Maximum Strap Tension	784N (178lbs)
Table Height	432mm (17")
Tensioning Range	Up to 40 kg (88 lbs)
Strapping Speed	1.8 seconds/strap
Strapping Used	5,6,9,12, 15.5mm (1/4, 3/8, 1/2, 5/8")
Power Supply	100-120, 200-240V Single Phase, 50-60Hz
Arch Size	W 850 mm x H 600 mm (W 33" x H 24")
Machine Dimensions	W 2161mm x H 1141mm x D 609mm (W 85" x H 44 7/8" x D 24")