

MODEL SBA 800

MANUAL STRETCH-BANDER



Features

- Fully Guarded Frame
- 70 RPM Ring
- Full Wrapping
- Banding
- Simple and Safe Operation
- Reliable and Easy to Maintain
- Reducing Packaging Cost
- No Product Damage Like Strap and String
- No Residue Like Tape
- Improves Production Rate
- Holds Product Firmly
- Other Speeds Available

MODEL SBA 800

MANUAL STRETCH-BANDER

Standard Features

- Power on/off switch
- Emergency stop button
- Clamp open/close
- Foot pedal - for continuous wrap
- Band selector (4,6,8)
- Full product wrap
- Ring jog
- Cycle start
- PLC control
- Automatic clamp/cut
- Easy and fast film tension adjustment
- Low maintenance
- Safety door for film loading with cut out switch

Applications

- Wood Molding
- Plastic Tubes
- Plastic Extrusions
- Aluminum Extrusions
- Windows
- Frames
- Paper Products
- Newspaper Bundles
- Frames
- Printed corrugated
- Textile rolls
- Siding
- Carpets
- Furniture
- Mill work
- Rods + pipes
- Band products to corrugated supports (ie. motors, electrical panels)
- Close boxes

Represented By:



SBA 800-05/12-100448


Available Options

- Various ring sizes
- Powered conveyor
- Manual side guides and hold downs
- Automatic side guides and hold downs
- Film tail wiper

Specifications

Electrical Supply:	120 VAC, single phase, 15 AMP,
	60 Hz with neutral
	TEFC, motors
Ring and Frame Specifications	Programmable Logic Controller
	Heavy duty ring gear
	Long lasting pinion gear
	TEFC, drive motor (HP depends on ring size)
Carriage and Film Specifications	Durable, heavy steel construction stands up to the toughest applications.
	Acrylic safety guards restrict access to wrap-zone while providing excellent visibility
	3-4-5" Film Width up to 8" diameter core diameter 3"
Pneumatic Requirements	Quick film roll change from 3" to 5"
	Easy and fast film tension adjustment
Pneumatic Requirements	45 Psi, clean, dry air

Maximum Product Sizes



Bander with 12.75" Ring I.D diameter and 1 HP Drive

